



## 15 Days Sample Leadtime Aluminum Heat Sink With Anodized Surface Treatmentment

Our Product Introduction

for more products please visit us on [alu-heatsink.com](http://alu-heatsink.com)

### Basic Information

- Place of Origin: China, Guangdong
- Brand Name: No Brand
- Minimum Order Quantity: 300kilogram
- Packaging Details: protect film
- Delivery Time: 15-30days
- Payment Terms: L/C, T/T



### Product Specification

- Mounting Type: Vertical
- Surface Treatmentment: Anodized, Customized
- Alloy: 6063
- Sample: Available
- Sample Leadtime: 15 Days
- Compatibility: Universal
- Durability: High
- Dimensions: Various Sizes Available
- Highlight: **Anodized Surface Treatment Aluminum Heat Sink**  
, Anodized Surface Treatment Heat Sink



### More Images



## Product Description

### Product Description:

The Aluminum Heatsink is a high-quality solution for heat dissipation in various applications, such as LED lighting fixtures, power electronics, and more. With a sample lead time of 15 days, this product offers quick availability to meet your project timelines. Designed as a heat sink extrusion, this aluminum heatsink is optimized for efficient heat transfer, ensuring your electronic components remain cool and perform at their best. The surface treatment options include anodized finish, which not only enhances the heatsink's aesthetics but also provides corrosion resistance for long-lasting performance. Customized surface treatments can also be accommodated to meet your specific requirements.

With various sizes available, the Aluminum Heatsink can be tailored to fit different applications and space constraints. Whether you need a compact heatsink for a small LED fixture or a larger one for power electronics, there is a size option to suit your needs. One of the key advantages of this product is its high durability. Constructed from high-grade aluminum, the heatsink is built to withstand rigorous thermal conditions and frequent use. This durability ensures a reliable and long-lasting cooling solution for your devices. The mounting type for this heatsink is vertical, allowing for easy installation and optimal heat dissipation in a vertical orientation. Whether you are designing a new product or upgrading an existing one, the vertical mounting type offers flexibility in placement and efficient thermal management.

In summary, the Aluminum Heatsink is a versatile and durable cooling solution suitable for a range of applications. With its heat sink extrusion design, customizable surface treatments, various sizes, high durability, and vertical mounting type, this product offers the performance and reliability you need to keep your electronic components cool and operating efficiently.

### Features:

Product Name: Aluminum Heatsink  
Mounting Type: Vertical  
Sample: Available  
Alloy: 6063  
Surface Treatment: Anodized, Customized  
Compatibility: Universal

### Technical Parameters:

Alloy	6063
Durability	High
Sample Leadtime	15 Days
Sample	Available
Dimensions	Various Sizes Available
Mounting Type	Vertical
Compatibility	Universal
Thermal Conductivity	High
Surface Treatment	Anodized, Customized

### Applications:

Product Application Occasions and Scenarios for the Aluminum Heatsink:

The Aluminum Heatsink by No Brand, originating from China, Guangdong, is a versatile product suitable for various applications in different scenarios.

One of the key application occasions for this product is in power stations. The high durability of the aluminum heatsink, made from alloy 6063, makes it ideal for use in power stations where heat dissipation is crucial for the efficient functioning of equipment.

Another important scenario where the aluminum heatsink excels is in heat sink extrusion applications. The anodized surface treatment enhances the heat dissipation capabilities of the heatsink, making it a reliable choice for heat sink extrusion processes.

Whether it is for industrial machinery, electronic devices, or LED lighting fixtures, the aluminum heatsink offers exceptional performance and reliability. The customizable surface treatment options allow for tailored solutions to meet specific requirements in various industries.

With packaging details including a protect film and a delivery time of 15-30 days, customers can expect their orders to arrive safely and within a reasonable timeframe. The payment terms of L/C and T/T provide flexibility for convenient transactions.

Furthermore, customers have the option to request a sample of the aluminum heatsink, with a sample lead time of 15 days. This allows for testing and evaluation before making bulk purchases, ensuring satisfaction with the product.

### Customization:

Product Customization Services:  
Brand Name: No Brand  
Place of Origin: China, Guangdong

Packaging Details: protect film  
Delivery Time: 15-30 days  
Payment Terms: L/C, T/T  
Alloy: 6063  
Compatibility: Universal  
Surface Treatment: Anodized, Customized  
Mounting Type: Vertical  
Sample Leadtime: 15 Days

**Packing and Shipping:**

Product Packaging:  
The Solar Photovoltaic Panels Frame Alu Profile is carefully packaged to ensure safe delivery.  
Shipping:  
Ocean, Air, Express



Golden Chain Products Industrial Co., Ltd.



+86 13823492359



cherry@jkd888.com



alu-heatsink.com