



# 6063 Alloy LED Lighting Samples Aluminum Heatsink High Thermal Conductivity

## **Basic Information**

• Place of Origin: China, Guangdong

Brand Name: No Brand
Packaging Details: protect film
Delivery Time: 15-30days
Payment Terms: L/C, T/T



## **Product Specification**

Mounting Type: VerticalAlloy: 6063

Sample: Available

Dimensions: Various Sizes Available
Surface Treatmentment: Anodized, Customized

Durability: HighThermal Conductivity: HighCompatibility: Universal

• Highlight: 6063 LED Aluminum Heatsink,

**High Thermal Conductivity LED Aluminum** 

Heatsink



# More Images



## **Product Description:**

The Aluminum Heatsink is a high-quality heat sink extrusion designed for efficient heat dissipation in various applications, including LED. lighting and power stations. With its high thermal conductivity, this heatsink is capable of effectively dissipating heat generated by electronic components, ensuring optimal performance and longevity.

The mounting type of this heatsink is vertical, allowing for easy installation and effective heat dissipation in a vertical orientation. Its universal compatibility makes it suitable for a wide range of electronic devices and applications, providing versatility and convenience for different projects and installations.

This aluminum heatsink is known for its durability, offering long-lasting performance and reliability even in demanding environments. It is built to withstand high temperatures and heavy usage, making it a dependable choice for critical applications where heat management is crucial.

With a sample lead time of 15 days, this heatsink provides a quick and efficient solution for your thermal management needs. Whether you are designing a new product or upgrading an existing system, this heatsink offers a reliable and effective thermal management solution with a fast turnaround time.

#### Features:

Product Name: Aluminum Heatsink - -

Surface Treatmentment: Anodized, Customized

Durability: High Compatibility: Universal Sample: Available

Thermal Conductivity: High

#### **Technical Parameters:**

Compatibility	Universat
Mounting Type	Vertical
Alloy	6063
Durability	High
Dimensions	Various Sizes Available
Surface Treatment	Anodized, Customized
Sample	Available
Thermal Conductivity	High
Sample Leadtime	15 Days

### **Applications:**

Product Application Occasions and Scenarios for the Aluminum Heatsink:

The Aluminum Heatsink, manufactured in Guangdong, China, is a high-quality heat sink extrusion designed for various applications. With its high thermal conductivity and durable construction, this product is suitable for a wide range of scenarios.

One key application occasion for this heatsink is in power stations. The efficient thermal conductivity of the aluminum heatsink helps in dissipating heat generated by electronic components in power stations, ensuring optimal performance and reliability.

Another scenario where the Aluminum Heatsink excels is in industrial settings where heat management is crucial. Its vertical mounting type allows for easy installation and effective heat dissipation, making it ideal for use in factories, manufacturing plants, and other industrial facilities

Whether it's for LED lighting fixtures, automotive electronics, or power supply units, this heatsink offers versatility in terms of dimensions, with various sizes available to suit different requirements. The product is shipped with protective film packaging to ensure it reaches customers in perfect condition.

Customers can expect a prompt delivery time of 15-30 days, along with flexible payment terms such as L/C and T/T. For those interested in sampling the product first, a sample lead time of 15 days is provided to experience the high durability and efficiency of the Aluminum Heatsink.











