



Sample Leadtime 15 Days Aluminum Heatsink for Universal Compatibility

Our Product Introduction

for more products please visit us on alu-heatsink.com

Basic Information

- Place of Origin: China, Guangdong
- Packaging Details: protect film
- Delivery Time: 15-30days
- Payment Terms: L/C, T/T



Product Specification

- Compatibility: Universal
- Alloy: 6063
- Mounting Type: Vertical
- Dimensions: Various Sizes Available
- Sample Leadtime: 15 Days
- Thermal Conductivity: High
- Durability: High
- Sample: Available
- Highlight: universal aluminum heatsink,
15-day leadtime heatsink,
aluminum heatsink with warranty

Product Description

Product Description:

The Aluminum Heatsink is a high-quality product designed for efficient heat dissipation in various applications, including power stations, LED lighting systems, and more. With its universal compatibility, the heatsink is suitable for a wide range of electronic devices and equipment.

Made from durable 6063 alloy, this heatsink offers excellent thermal conductivity and heat dissipation capabilities. The use of 6063 alloy ensures reliable performance and long-lasting durability, making it an ideal choice for demanding thermal management applications. Available in various sizes, the Aluminum Heatsink allows for flexible installation options to accommodate different space constraints and thermal requirements. Whether you need a compact heatsink for small devices or a larger one for high-power applications, there is a size available to suit your needs.

The mounting type of the heatsink is vertical, providing a stable and secure attachment to the heat-generating component. This vertical mounting design helps optimize airflow and thermal performance, ensuring efficient cooling of the target device.

For enhanced durability and corrosion resistance, the heatsink features an anodized surface treatment. The anodized finish not only adds a sleek look to the heatsink but also provides protection against environmental factors, ensuring long-term performance in various operating conditions.

Additionally, the surface treatment of the Aluminum Heatsink can be customized to meet specific aesthetic or functional requirements. Whether you need a specific color, texture, or coating for your application, the heatsink can be customized to match your preferences and design specifications.

In conclusion, the Aluminum Heatsink offers a versatile and reliable solution for thermal management in power stations, LED lighting systems, and other electronic devices. With its universal compatibility, durable 6063 alloy construction, various sizes available, vertical mounting type, and anodized surface treatment, this heatsink is an excellent choice for optimizing heat dissipation and ensuring the efficient operation of your equipment.

Features:

Product Name: Aluminum Heatsink

Compatibility: Universal

Durability: High

Sample Leadtime: 15 Days

Thermal Conductivity: High

Surface Treatment: Anodized, Customized

Technical Parameters:

| | |
|-----------------------|-------------------------|
| Surface Treatmentment | Anodized, Customized |
| Durability | High |
| Thermal Conductivity | High |
| Mounting Type | Vertical |
| Sample Leadtime | 15 Days |
| Sample | Available |
| Alloy | 6063 |
| Compatibility | Universal |
| Dimensions | Various Sizes Available |

Applications:

The Aluminum Heatsink product, originating from China, Guangdong, is a versatile solution ideal for a variety of Product Application Occasions and Scenarios. Its durable nature makes it suitable for use in demanding environments such as LED Lighting, Power stations, and industrial settings where high thermal conductivity is essential.

With a high level of durability, this Aluminum Heatsink is designed to withstand prolonged use and harsh conditions, making it a reliable choice for applications that require long-term performance. The surface treatment options, including anodized and customized finishes, allow for enhanced protection and customization to suit specific requirements.

For Packaging Details, the product is carefully packaged with a protect film to prevent any damage during transportation, ensuring it arrives in pristine condition. The Delivery Time ranges between 15-30 days, offering a prompt turnaround for orders. Payment Terms include L/C and T/T, providing flexibility for customers to choose the most convenient option.

The Aluminum Heatsink's mounting type is Vertical, making it easy to install and integrate into different systems or structures. Its high thermal conductivity ensures efficient heat dissipation, making it an ideal choice for applications where heat management is crucial, such as LED Lighting and Power stations.

In addition, samples are available for customers to evaluate the product before making a larger purchase, ensuring satisfaction with the quality and performance. Overall, the Aluminum Heatsink is a reliable and versatile solution for various Product Application Occasions and Scenarios, offering high durability, efficient heat dissipation, and customization options to meet diverse needs.



Golden Chain Products Industrial Co., Ltd.



+86 13823492359



cherry@jkd888.com



alu-heatsink.com